

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
26 May 2005 (26.05.2005)

PCT

(10) International Publication Number  
WO 2005/046852 A3

(51) International Patent Classification<sup>7</sup>: F23D 11/16

(21) International Application Number: PCT/US2004/037450

(22) International Filing Date: 8 November 2004 (08.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 60/518,379 7 November 2003 (07.11.2003) US

(71) Applicant (for all designated States except US): COHESION TECHNOLOGIES, INC. [US/US]; 2500 Faber Place, Palo Alto, CA 94303 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ABBATE, Anthony, J. [US/US]; 4346 Headen Way, Santa Clara, CA 95054 (US). PHUNG, Phu [—/US]; 33081 Calistoga Street,


(74) Agents: REED, Dianne, E. et al.; Reed Intellectual Property Law Group, 800 Menlo Avenue, Suite 210, Menlo Park, CA 94025 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,

[Continued on next page]

(54) Title: DEVICE AND METHOD FOR MIXING AND DISPENSING FLUID COMPONENTS OF A MULTICOMPONENT COMPOSITION



WO 2005/046852 A3

(57) Abstract: Provided are devices and methods for dispensing a multicomponent composition comprised of a mixture of a plurality of different fluid components. A diffuser surface is placed downstream from a plurality of inlets. An outlet extends through the diffuser surface. At least one inlet placed in fluid communication with a source of pressurized carrier fluid, and each of a plurality of inlets is placed in fluid communication with a source of a different fluid component. Once the diffuser surface receives fluid components, each received fluid component is directed toward the outlet for mixing and dispensing therethrough by the pressurized carrier fluid from the carrier fluid inlet. Typically, the fluid components are maintained in a different flow path on the diffuser surface before mixing.



SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

- *with international search report*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

**(88) Date of publication of the international search report:**

7 July 2005